



Diesel screw pump, with a powerful 19 kw STAGE V engine. Complies with current emissions regulations, established for the European Union.

Easy-to-maintain, engine offering high performance for plastering and self-levelling.

Perfect for continuous pumping of material up to 6mm granulometry.

Easy to clean; due the both direction of rotation, it allows easy removal of plugs.

Maneuverable and easy to transport, due to its compact design.

All our mortar machines can be combined with various accessories to perform more services.

- CE certificate
- Warranty certificate

Simple, robust and very easy to handle. Multiple applications; pumping, injection, and projection

- . Mixing mortar
- . Plastering bagged mortars
- . Plastering traditional mortars
- . Self-leveling mortar
- . Mortar injection

MORTER VH2

TECHNICAL DATA

MORTER FAMILY

RENDIMIENTOS

Model
Engine
Power
Pumping distance*
Pumping height*
Max grain size*
Pumping pressure*
Loading height
Hopper capacity
Mixer capacity
Dimensions/mm
Weight
Sator & rotor size

VH 2
Diesel Stage V
19 Kw
180 mts
70 mts
6 mm
* 30 bar
800 mm
100 L
110x63 mm
2500x1300x800
750 Kg
1L6 ; 2L6

*Depends on consistency, quality and composition of the material, pump model and condition, diameter and length of the transport hose and pumping height of the material.