



Compact concrete pump

UF-15 is a lightweight and robust concrete pump, ideal for transporting fine concrete, fluid screed, and sprayed concrete. Its compact design and Hatz

3-cylinder diesel engine (18.4 kW) make it efficient and economical,

complying with Euro Stage V regulations.

Versatility: Processes aggregates up to 16 mm with a flow rate of 12 m³/h.

Efficiency: Smooth and impact-free transport thanks to its optional air

chamber and low-wear pistons.

Reliability: Easy maintenance with durable components and accessible

spare parts.

Comfort: Intuitive digital controls and lightweight design for challenging

locations.

Optional accessories: GPS, work lights, anti-theft device, among others.

Ideal for projects requiring precision, flexibility, and superior performance.

UF SC TRAILER

TECHNICAL DATA

UF-15

PERFORMANCE

Maximum volume output*

12m³/h

Maximum concrete pressure

35 bar

Maximum aggregate size

15mm

Hydraulic pump

Gear pump 30 cc

High and low pressure

Low pressure

Hydraulic circuit

Open

Delivery distance :

150m

*Horizontal

Delivery distance :

100m

*Vertical

Pumping cylinders

125 mm

Diameter of hydraulic cylinder

70/40 mm

Maximum strokes per minute

30

Variable volume control

From 0 to full load

Diameter of S-valve

100 mm

Number of shift cylinders

2

Hydraulic tank capacity

40 L

Hopper height

1,20 m

Hopper capacity

250L

Outlet diameter

100mm

ENGINE

Manufacturer's model

Hatz

Water-cooled

Water-cooled

Horsepower

19 Kw

Fuel tank capacity

40L

Axel

2

Axle support capacity

2.000 Kg

Tires - load range

*

Brakes

Mechanically

Outriggers

1-Manual

DIMENSIONS

Length

3800 mm

Width

1330 mm

Height

1550 mm

Weight (approx.)

(Aprox): 1350 Kg

* Distancia de bombeo, siempre depende de el tipo de materiales usado, humedad, temperatura etc...